

APPLICATION FOR UNITED STATES LETTERS PATENT

by

LARRY D. WOODRING

for

**SYSTEMS AND METHODS FOR PROVIDING USER PROFILE INFORMATION IN
CONJUNCTION WITH AN ENHANCED CALLER INFORMATION SYSTEM**

SHAW PITTMAN LLP
1650 Tysons Boulevard
McLean, VA 22102-4859
(703) 770-7900
Attorney Docket No.: BS01-379

09964299.092901
702260"06249660

SECRET

09/964392

Field of the Invention

Background of the Invention

1

is, subscribers typically cannot access the information stored by the caller-id device without being physically present to operate the device. Another problem with conventional caller-id services is the limited amount of information provided to subscribers. Caller-id devices and public switched telephone network (PSTN) systems that provide conventional caller-id services typically support only text messages. Moreover, the text messages are typically limited to fifteen text-based characters. Caller-id devices typically have only a limited amount of memory so as to make them inadequate for long-term record-keeping purposes.

[0005] Some in the art have sought to overcome some of these problems by designing computer-based software and hardware systems which are connected to the subscriber's telephone line. When an incoming call is received, the signal destined for the caller-id device is intercepted and the information can be input into a database to make a log of all inbound calls. These systems have been known to fail and result in the subscriber's telephone being tied up until the subscriber is made aware of the problem. Also, such end-user solutions do not take full advantage of multimedia resources available via modern communications networks.

SUMMARY OF THE INVENTION

[0006] Embodiments of the present invention comprise systems and methods for providing user profile information in conjunction with an enhanced caller information system. The methods include provisioning a trigger on a subscriber's telephone line at a service switching point (SSP) and receiving a call from a caller to the subscriber at the subscriber's SSP. In response to the trigger, the SSP sends a query to a service control point (SCP). Upon receiving the query, the SCP sends an information

message to a server for delivery to the subscriber upon request. The information message may include, for example, calling number, calling name, caller's address, caller's location (for mobile callers), calling date, calling time, call length, call ending time, and the like. The information on the server can be cross-referenced with other useful information such as a map of the caller's address or location.

[0007] Systems embodying the present invention may include a trigger provisioned on a subscriber's telephone line at the subscriber's SSP. When the SSP receives a call for the subscriber, the call hits the trigger, causing the SSP to send a query to an SCP. The query includes calling party number information and called party number information. The SCP responds to the query in the usual manner (e.g., by providing calling name information, if available), and additionally, the SCP sends an information message to a server. The server stores the information received from the SCP and, upon request, provides the subscriber with enhanced caller-id information. The server may also be used to maintain long-term logs recording the subscriber's caller activity. Additionally, the subscriber may download caller information for use with other applications.

[0008] Embodiments of the present invention may also be implemented for wireless subscribers and/or wireless callers. Further, embodiments may include servers adapted for access via the worldwide web or other commonly used applications accessible via communications networks, such as, for example, the Internet. In another embodiment the server may be adapted to provide information to the subscriber via a wireless device. In another embodiment a subscriber may access the server via a telephone call and receive calling information via voice message.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0009] FIG. 1 is a schematic diagram showing the operation of an exemplary embodiment of the present invention.
- [0010] FIG. 2 is a schematic diagram showing the operation of another exemplary embodiment of the present invention.
- [0011] FIG. 3 is a schematic diagram showing the operation of another exemplary embodiment of the present invention.
- [0012] FIG. 4 is a schematic diagram showing the operation of another exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF AN EMBODIMENT OF THE INVENTION

- [0013] Embodiments of the present invention allow users to submit profile information providing enhanced caller information that may be accessed by others during or after a telephone call. Embodiments of the present invention utilize AIN systems and data network servers to provide a server-based enhanced caller information service. The service enables subscribers to receive selected profile information in addition to standard calling number and calling name records for incoming calls. Examples of user profile information may include photos, links to personal web sites, images of business cards, or other multi-media content. By receiving such user profile information together with caller identification information, subscribers may be provided with a full range of detailed information and graphical images related to the calling party.

[0014] In embodiments of the present invention the server comprises a caller information application adapted or programmed to receive information from users and to provide the information to subscribers of the service in conjunction with caller information services. In exemplary embodiments of the present invention the server may be a web-server allowing subscribers to monitor their telephone records from any location from which access to the server is available. In other exemplary embodiments, the server may comprise, for example a mail server or a file transfer server, accessed by subscribers and users via client application programs installed on their local computer systems.

[0015] As used herein, the terms "caller" and "user" are both used to refer to a person, company, organization, or other entity that provides user profile information to be presented to a subscriber in conjunction with enhanced caller information according to the present invention. As used herein, "subscriber" refers to a person, company, organization, or other entity that receives user profile information in conjunction with enhanced caller information according to the present invention.

[0016] FIG. 1 is a schematic diagram showing an exemplary embodiment of the present invention. In this embodiment caller 10 uses computer 15 to login to server 40 to provide or update user profile information. For example, user 10 may provide her photograph and photographs of her home and children. User 10 may opt to include other personal information, including, for example, a favorite quote, biographical information, and itinerary data for a planned trip. In another example, user 10 may include directions to his or her home or other detailed information. In yet another example, user 10 may provide an image of a business card or other

identifying information. If, for example, user 10 is a business or other such entity, profile information may include a link to the company's web site, advertising information, pictures of products, or other multi-media advertising information.

[0017] Caller 10 may setup his or her user profile to provide enhanced caller information to one or more called parties. That is, for example, the user profile may include one or more lists of full access called parties (identified, e.g., by a party's directory number (DN)), one or more lists of partial access called parties, and one or more lists of blocked access called parties. User 10 may include a default access level such that any called numbers not on any higher level list will receive only the default information which may comprise no information. For example, whenever caller 10 calls a party (i.e., dials the party's DN) on a full access list, the called party receives or may access all of user 10's profile information. In contrast when caller 10 calls a party on a different access list, the called party will only receive or access that material specifically allowed by user 10. Caller 10 may implement such multi-levels of access to control how much information is provided to called parties. This may be useful, for example, if user 10 include highly personal information in his or her profile.

Operation of an Exemplary Embodiment

[0018] When caller 10 uses telephone 11 to place a call to subscriber 20, caller-id device 23 may receive the calling name and/or calling number information as it would in conventional caller-id services. However, in addition to sending the information to caller-id device 23, AIN 30 also sends the information to server 40.

[0019] Server 40 may be accessible from any computers used by user 10 or subscriber 20, such as, for example, computer 15 (located at user 10's premises) or computer 24 (located at subscriber 20's premises). As shown in Fig. 1, server 40 may be directly accessible by computers 15 and 24, or may be accessible via network 50. Network 50 may be any data communications network, such as, for example the well-known Internet. Additionally, user 10 or subscriber 20 may use some other computer 60 or wireless device 26 to provide or obtain the caller information via network 50, or direct access if server 40 is so configured.

[0020] Server 40 may optionally include access control systems to maintain the users' and subscribers' privacy. For example, server 40 may be programmed to verify user 10's identity and authorization prior to allowing the user profile information to be updated. Similarly, server 40 may be programmed to prompt subscriber 20 for a valid username and password or other security tokens before providing any information about callers to the subscriber's telephone line.

[0021] Fig. 1 shows caller 10 having wireline 12 connected to service switching point (SSP) 32. However, as would be apparent to those skilled in the art, caller 10 could be calling from any telephony device, including, for example, a wireless telephone, a wireless interactive pager, an Internet calling device, and the like. When the call reaches subscriber 20's central office, SSP 31, it encounters trigger 31a provisioned on subscriber 20's wireline 22. As a result, SSP 31 issues a query to service control point (SCP) 33 via signaling network 34. As known in the art, the trigger may be a termination attempt trigger (TAT) or some other suitable trigger for initiating a query to SCP 33. Also as known in the art, signaling network 34 may be the well-known

2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2

[0023] Server 40 may combine information received from SCP 33 and the user profile information received from user 10 with other information to enhance the caller-id service. For example, server 40 may provide additional geographical information such as the postal zip code of the caller or the caller's county, state, or country. Such information may be compiled and stored in database 45 and cross-referenced with the calling number and calling name information as needed. Similarly, server 40 may rearrange the information according to the subscriber's display preferences. For example, server 40 may provide a sort option to display information according to the date/time of the calls, by calling party number, by calling name, by geographic location, by area code, or other criteria.

8

the prior month's calls. Another report may provide a breakdown of calls, for example, by time of day, by calling number, or other criteria.

[0025] In another embodiment of the present invention, SCP 33 may provide follow-up information regarding incoming calls. For example, after a call has ended, SCP 33 may send a message to server 40 indicating the length of the call. SCP 33 may also provide detailed information such as the circuit and trunk id for the call. In an exemplary configuration of this embodiment, SCP 33 may respond to SSP 31's query in the usual manner and also issues a Monitor-for-Change query, or other suitable instruction, to SSP 31. In response to the instruction SSP 31 monitors subscriber line 22 for a change in status (such as the line becoming idle after a call has ended). When SSP 31 detects the change in status it reports the event to SCP 33. SCP 33 may use this information, in conjunction with the original query to compute a call duration. The call duration may then be included in an information message sent from SCP 33 to server 40.

[0026] In an alternative embodiment, the server may include text-to-speech functionality allowing the subscriber to retrieve suitable portions of the caller information using any telephone device. Fig. 2 is a schematic diagram showing an exemplary configuration for this embodiment. Like numbered elements in Fig. 2 perform substantially the same functions are described above. Server 47 allows subscriber 20 to check for incoming calls placed to his or her telephone line 22. Using any telephone, such as, for example, telephone 51 or mobile telephone 52, subscriber 20 can call server 47 to hear a summary of inbound calls placed to wireline 22. This embodiment may incorporate an interactive voice response system

providing a menu of options available to subscribers. Further, as shown in Fig. 2, subscriber 20 may still access the full enhanced caller information using, for example, computer 24.

[0027] Fig. 3 is a schematic diagram showing another exemplary embodiment of the present invention. This embodiment includes many of the same elements as shown in Figs. 1 and 2. However, instead of the subscriber having a separate caller-id device and a wireline, in this embodiment, the subscriber has a wireless telephone 25 with integrated caller-id services. As shown in Fig. 3, when caller 10 places a call to wireless telephone 25, it eventually reaches mobile switching center (MSC) 70 for delivery to wireless telephone 25 via wireless connection 71. Just as with wireline systems, trigger 70a on the subscriber's "line" may be provisioned at MSC 70. MSC 70 issues a query to SCP 33 via signaling network 34 in response to the trigger. Accordingly, when the incoming call reaches MSC 70, it sends a query to SCP 33. As described above, SCP 33 responds to the query as it normally would, but also sends caller-id information (for example, called party number, calling name and calling number) to server 40. The information sent by SCP 33 to server 40 in this embodiment may include any of the information already described above.

[0028] Fig. 4 is a schematic diagram showing another embodiment of the present invention. In this embodiment, the caller uses wireless telephone 13 and wireless connection 14 to call subscriber 20 via MSC 71. In this embodiment, MSC 71 is programmed to include the caller's geographic location information in a field of the initial address message (IAM) used to setup the call with SSP 31. This call encounters trigger 31a on subscriber 20's line 22 causing SSP 31 to issue a query to

SCP 33. SSP 31 includes the location information in the query message for processing by SCP 33. Such information could be based on the cell-site from which the caller is calling or if emergency 911 services are implemented, a more precise location could be provided. SCP 33 includes the caller-id information (i.e., calling number, calling name, and the physical location of the caller) in the message sent to server 40.

[0029] In addition to providing detailed multi-media information to subscribers and near real-time views of incoming call information, the present invention provides a permanent or long-term log of all incoming call information in a database stored by the service provider. As described above, a subscriber may download this log onto a computer for historical or other uses. For example, a subscriber could use the information to bill callers for the time spent on the telephone. Additionally, the caller information and historical log information could be integrated with other applications on the subscriber's computer, for example, address books, time-keeping logs, and the like. The information captured may be used in conjunction with existing web information services to create complete entries in address books such as those associated with email applications. Moreover, the information may be used to perform various business analyses such as geographic and demographic analysis of callers.

[0030] Servers used in embodiments of the present invention may include, e.g., web servers, email servers, file transfer protocol servers (FTP), and the like. Users and subscribers may use any suitable client or server application to access and receive data from the server.

